

# Synlawn Comfort CoolPlus Elite



**TRAFFIC**  
★★★★★



**SOFTNESS**  
★★★★★



**NATURAL LOOK**  
★★★★★

The ultimate in durability and softness. Suitable to any landscape application. A revolutionary and advanced concept in synthetic turf.

Constructed of new and exclusive texturised yarn with entanglement technology, a first in synthetic turf. It is highly resistant to pile crush even with high traffic situations.

Can be used as a true non-sand infill product if required.

Such is the quality and durability of Comfort Elite it carries an unprecedented lifetime warranty.

No other synthetic turf made comes close to Comfort Elite.

Australian Made Coolplus yarn cooling technology for up to 30% cooler surface temperature. 3.71 metres wide – Lifetime warranty. Australian Made with APT Australian Made yarns.



## Features

-  Contaminant free polymers
-  UV stabilised
-  Compatible pigments
-  ISO Quality Assurance
-  First quality raw materials
-  Heat stabilised
-  Developed for the Australian sports and landscaping market
-  Warranty
-  Precise synergistic formula
-  No heavy metals in pigments
-  25 years exposure testing in Australian environment
-  Do you know where your yarn comes from?

### Finished Product Details

Application: Synthetic lawns / Leisure / Commercial  
 Pile Height: 50mm  
 Colours Available: Field Green / Beige with brown sub - pile  
 Total Product Weight: 2676 g/m<sup>2</sup>

### Yarn Properties

Yarn Construction: Coolplus PE Monofilament & PP sub – pile combination  
 Linear Density: 600 Tex & 490 Tex sub - pile  
 Environment: Environmentally friendly yarns which are heavy metal free  
 UV Stability: The yarn is protected against UV degradation to the highest level and light fastness meets the highest standards

### Configuration

Machine Gauge: 12.7mm (1/2")  
 Stitch Rate: 16 per 100 mm  
 Yarn Weight: 1706 g/m<sup>2</sup>  
 No. of Tufts: 12,598m<sup>2</sup>  
 Perforated: Standard

### Primary Backing

Construction: UV resistant, non-fibrillated plain polypropylene  
 Primary Layers: Dual

### Secondary Coating

Compound Base: Hybrid Emulsion  
 Tuft Anchorage: 40 Newtons (minimum)  
 Antioxidising Agent: Present

### Supply

Available Width: 3.71m  
 Standard Roll Length: 20.0 lineal metres  
 Approx. Shipping Weight: 9.8 kg/lm  
 Line Systems: N/A

### Infill Material

Stabilising Infill: Fine grade silica sand  
 Performance Infill: N/A

### Product Warranty

Lifetime warranty as per manufacturer's standard warranty terms.  
 Manufactured in Australia